

## Methyl ethyl ketone (MEK)

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

<b>Trade name</b>	Methyl ethyl ketone (MEK)		
<b>Synonyms</b>	2-Butanone, 3-Butanone, methyl acetone, Ethyl methyl ketone		
<b>Use</b>	Catalyst production, Industrial & Institutional cleaning, Industrial use, Intermediate, Paint and Coatings, Pharmaceutical, Process/Extraction Solvent, Process material, Raw material for chemical processes, Raw material for industry, Raw material for pharmaceuticals, Solvent		
<b>Company</b>	Sasol Chemicals (USA) LLC (an affiliate of Sasol Chemicals North America LLC)		
<b>Address</b>	12120 Wickchester Lane, Houston, TX 77079		
<b>Telephone</b>	CHEMTREC North America Transportation Emergency (24-hr)		+1 (800) 424 9300
	CHEMTREC World Wide		+1 (703) 527-3887
	Other Emergencies (24-hr)		+1 (337) 494 5142
	SDS and Product Information (8:00am-4:30pm CST)		+1 (281) 588 3491
	Health and Safety Information (7:30am-4:00pm CST)		+1 (281) 588 3492
<b>E-mail address</b>	ProdSafe.Shared@sasol.com		

### SECTION 2 HAZARDS IDENTIFICATION

<b>OSHA/GHS Hazards</b>	Flammable liquids	Category 2
	Eye irritation	Category 2A
	Specific target organ toxicity - single exposure	Category 3 (Narcotic effects)

#### LABEL ELEMENTS

##### Hazard symbols



**Signal word** Danger

**Hazard statements** H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

##### Precautionary statements

**Prevention** P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

## Methyl ethyl ketone (MEK)

---

P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P280 Wear protective gloves/ eye protection/ face protection.  
P264 Wash skin thoroughly after handling.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.

**Response** P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312 Call a POISON CENTER/doctor if you feel unwell.

**Storage** P403 + P405 + P235 Store locked up in a well-ventilated place. Keep cool.

---

### SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

---

<u>Components</u>	<u>CAS-No.</u>	<u>Weight percent</u>
Methyl ethyl ketone	78-93-3	99.5

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.

---

### SECTION 4 FIRST AID MEASURES

---

**Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.

**Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of shortness of breath, give oxygen. Call a physician immediately.

**Ingestion** If swallowed, call a poison control centre or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

## Methyl ethyl ketone (MEK)

---

### SECTION 5 FIREFIGHTING MEASURES

---

#### FLAMMABLE PROPERTIES

**Fire/explosion** Vapours may form explosive mixture with air. Flash back possible over considerable distance. Use water spray to disperse the vapors.  
NFPA Class 1B flammable liquid.

**Suitable extinguishing media** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**Protective equipment and precautions for firefighters** In the event of fire, wear self-contained breathing apparatus.

**Further information** Keep containers and surroundings cool with water spray. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### SECTION 6 ACCIDENTAL RELEASE MEASURES

---

**Methods and materials for containment and cleaning up** Evacuate personnel to safe areas. Remove all sources of ignition. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Do not flush into surface water or sanitary sewer system.

### SECTION 7 HANDLING AND STORAGE

---

**Safe handling advice** Ensure all equipment is electrically grounded before beginning transfer operations. Keep away from heat and sources of ignition.

**Storage/Transport pressure** Ambient

### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

---

#### ENGINEERING MEASURES

Air contaminant levels should be controlled below the PEL or TLV for this product (see Exposure Guidelines). Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment.

#### PERSONAL PROTECTIVE EQUIPMENT

**Eyes** Chemical resistant goggles must be worn. Face-shield.

**Skin** Wear suitable protective clothing, gloves and eye/face protection.

## Methyl ethyl ketone (MEK)

---

**Inhalation** Respiratory protection is normally not required except in emergencies or when conditions cause excessive airborne levels of mists or vapors. Use NIOSH approved respiratory protection.

### EXPOSURE GUIDELINES

<u>Components</u>	<u>Exposure limit(s)</u>
<b>Methyl ethyl ketone</b>	ACGIH TLV (8-hour) 200 ppm 590 mg/m <sup>3</sup> ACGIH STEL (Short Term Exposure Limit) 300 ppm 885 mg/m <sup>3</sup> OSHA PEL (Permissible Exposure Limit) 200 ppm 590 mg/m <sup>3</sup>

PEL= Permissible Exposure Limits  
TLV= Threshold Limit Value  
EL= Excursion Limit

TWA= Time Weighted Average (8 hr.)  
STEL= Short Term Exposure Limit (15 min.)  
WEEL= Workplace Environmental Exposure Level

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Appearance</b>	liquid
<b>Colour</b>	clear colourless
<b>Form</b>	liquid
<b>Odour</b>	characteristic
<b>Odour Threshold</b>	No data available
<b>Flash point</b>	-6 °C, 21 °F;
<b>Flammability</b>	Upper explosion limit: 11.5 %(V) Lower explosion limit: 1.5 %(V)
<b>Boiling point/boiling range</b>	79.6 °C, 175.6 °F;
<b>Melting point/range</b>	-86 °C, -123 °F;
<b>Auto-ignition temperature</b>	404 °C, 759 °F;
<b>Decomposition temperature</b>	No data available
<b>Flammability (solid, gas)</b>	No data available
<b>Vapour pressure</b>	126 hPa @ 25 °C, 77 °F;
<b>Vapour density</b>	1.15

**Methyl ethyl ketone (MEK)**

---

<b>Density</b>	0.805 g/cm <sup>3</sup> @ 20 °C, 68 °F;
<b>Relative density</b>	No data available
<b>Water solubility</b>	partly miscible
<b>Viscosity</b>	No data available
<b>Viscosity, dynamic</b>	0.40 mPa.s @ 20 °C, 68 °F; DIN 53015;
<b>pH</b>	No data available
<b>Evaporation rate</b>	No data available
<b>Partition coefficient: n-octanol/water</b>	log Pow: 0.3; @ 40 °C, 104 °F;
<b>Volatile organic compounds (VOC) content</b>	100 %

---

**SECTION 10 STABILITY AND REACTIVITY**

---

<b>Reactivity</b>	Vapours may form explosive mixture with air.
<b>Chemical stability</b>	No decomposition if stored and applied as directed.
<b>Conditions to avoid</b>	Extremes of temperature and direct sunlight.
<b>Hazardous decomposition products</b>	None known
<b>Materials to avoid</b>	Oxidizing agents.
<b>Hazardous polymerisation</b>	May form explosive peroxides.

---

**SECTION 11 TOXICOLOGICAL INFORMATION**

---

<b>Acute dermal toxicity</b>	LD50 Rabbit: > 2,000 mg/kg (literature value)
<b>Acute inhalation toxicity</b>	No data available
<b>Acute oral toxicity</b>	LD50 Rat: > 2,000 mg/kg (literature value)

**Methyl ethyl ketone (MEK)**

---

<b>Skin corrosion/irritation</b>	(Rabbit) slight irritation (literature value)
<b>Serious eye damage/eye irritation</b>	(Rabbit) irritating (literature value)
<b>Respiratory or skin sensitisation</b>	Guinea pig: not sensitizing; Maximisation Test (literature value)
<b>Germ cell mutagenicity</b>	<b>Genotoxicity in vitro:</b> Type: Ames test System: Salmonella typhimurium; with and without metabolic activation Result: In vitro tests did not show mutagenic effects (literature value)  <b>Genotoxicity in vivo:</b> No data available  <b>Assessment Mutagenicity:</b> Based on available data, the classification criteria are not met.
<b>Reproductive toxicity</b>	<b>Reproductive toxicity:</b> No data available  <b>Assessment Reproductive toxicity:</b> No data available  <b>Teratogenicity:</b> No data available  <b>Assessment teratogenicity:</b> No data available
<b>STOT - single exposure</b>	The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.
<b>STOT - repeated exposure</b>	No data available
<b>Aspiration toxicity</b>	No data available
<b>Carcinogenicity</b>	<b>Assessment carcinogenicity:</b> Contains no ingredient listed as a carcinogen

**Methyl ethyl ketone (MEK)**

---

**SECTION 12 ECOLOGICAL INFORMATION**

---

- Toxicity to fish** LC50 (Pimephales promelas (fathead minnow)) 96 hours: > 100 mg/l; static test (literature value)
- Toxicity to aquatic invertebrates** EC50 (Daphnia magna (Water flea)) 48 hours: > 100 mg/l; static test (literature value)
- Toxicity to algae** EC50 (Pseudokirchneriella subcapitata (green algae)) 96 hours: > 100 mg/l; static test (literature value)
- Biodegradation** Readily biodegradable.  
OECD Test Guideline 301D (28 d): > 60 %  
aerobic  
(literature value)
- Bioaccumulative potential** No bioaccumulation is to be expected (log Pow <= 4).
- Mobility in soil** No data available
- Other adverse effects** This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

---

**SECTION 13 DISPOSAL CONSIDERATIONS**

---

- Waste Code** U159.D001 - Ignitability (RQ 100 LB). Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification.
- Disposal methods** Dispose of only in accordance with local, state, and federal regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.
- Empty containers.** Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

---

**SECTION 14 TRANSPORT INFORMATION**

---

- DOT** UN 1193, Methyl Ethyl Ketone, 3, II  
When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.

**Methyl ethyl ketone (MEK)**

**IATA** UN 1193, Methyl Ethyl Ketone, 3, II  
When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.

**IMDG** UN 1193, Methyl Ethyl Ketone, 3, II  
When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

**Remarks** No data available

**SECTION 15 REGULATORY INFORMATION****U.S. FEDERAL REGULATIONS****TSCA Inventory Listing****Components**

2-Butanone

**CAS-No.**

78-93-3

All chemical substances in this product are either on the TSCA Active Inventory, or in compliance with the inventory.

**SARA 302 Status****Components****CAS-No.****Weight percent**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 311/312 Classification**

Should this product meet EPCRA 311/312 Tier reporting criteria of 40 CFR 370, refer to Section 2 of this SDS for appropriate classification and Section 3 for components that meet the hazardous classification.

**SARA 313 Chemical****Components****CAS-No.****Weight percent**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**US. EPA CERCLA Hazardous Substances (40 CFR 302)****Components**

2-Butanone

**Reportable Quantity**

5,000 LB

**Weight percent**

99.5 %

**INTERNATIONAL REGULATIONS****WHMIS Classification**

Flammable liquids

Category 2

Eye irritation

Category 2A

Specific target organ toxicity -

Category 3 (Narcotic effects)

single exposure

## Methyl ethyl ketone (MEK)

---

### European Union

Classification according to Regulation (EU) 1272/2008.

Flammable liquids, Category 2

Eye irritation, Category 2

Specific target organ toxicity - single exposure, Category 3 (Narcotic effects)

<b>Australia. Inventory of Chemical Substances (AICS)</b>	Listed
<b>Japan. Inventory of Existing and New Chemical Substances (ENCS)</b>	Listed
<b>Japan. ISHL - Inventory of Chemical Substances</b>	Listed
<b>Canada. Domestic Substances List (DSL) Inventory</b>	Listed
<b>Canada. Non-Domestic Substance Listing (NDSL)</b>	Not listed
<b>Philippines. Inventory of Chemicals / Chemical Substances (PICCS)</b>	Listed
<b>Korea. Existing Chemicals Inventory (KECI)</b>	Listed
<b>China. Inventory of Existing Chemical Substances (IECSC)</b>	Listed
<b>Mexico. National Inventory of Chemical Substances (INSQ)</b>	Listed
<b>New Zealand. Inventory of Chemical Substances (NZIoC)</b>	Listed
<b>Switzerland. Inventory of Notified New Substances (CHINV)</b>	Listed
<b>Taiwan. National Existing Chemical Inventory (NECI)</b>	Listed

Please note: The names and CAS numbers which are used for this product in the stated inventories may deviate from the information which is listed in Section 3.

### STATE REGULATIONS

California Prop. 65

Components

none

CAS-No.

## SECTION 16 OTHER INFORMATION

---

### HAZARD RATINGS

	<u>Health</u>	<u>Flammability</u>	<u>Physical Hazard/ Instability</u>
<b>HMIS®</b>	1	3	0
<b>NFPA</b>	1	3	0

**Methyl ethyl ketone (MEK)**

---

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR SASOL CHEMICALS (USA) LLC'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH SASOL CHEMICALS (USA) LLC CONSIDERS ACCURATE AND RELIABLE, SASOL CHEMICALS (USA) LLC MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.

---