

1 Identification of the substance and manufacturer

Trade name: TRUCK BED COATING
Product code: 0000200041
Product category: PC9a Paints and coatings.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178
 Phone: 815-895-9101 www.seymourpaint.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

#708 Page 1 of 4

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Carc. 1B H350 May cause cancer.
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.
 STOT SE 3 H336 May cause drowsiness or dizziness.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word
Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause cancer.

Precautionary statements

Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Do not handle until all safety precautions have been read and understood.
 Wear protective gloves.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a POISON CENTER/doctor if you feel unwell.
 If skin irritation occurs: Get medical advice/attention.
 IF ON SKIN: Wash with plenty of water.
 If eye irritation persists: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Protect from sunlight. Store in a well-ventilated place.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

74-98-6	propane	15.74%
67-64-1	Acetone	14.51%
8052-41-3	Stoddard Solvent	13.76%
106-97-8	n-butane	9.25%
110-19-0	isobutyl acetate	6.73%
110-54-3	hexane	6.23%
1330-20-7	xylene (mix)	5.65%
9006-04-6	RUBBER	3.67%
108-65-6	PM acetate	2.89%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing: Rinse out mouth and then drink plenty of water.

Safety Data Sheet

Printing date 02/08/2016

Revised On 02/08/2016

Trade name: TRUCK BED COATING

#708 Page 2 of 4

(Contd. of page 1)

Most important symptoms and effects:
Indication of any immediate medical attention needed:

Rinse mouth with water. Do not induce vomiting.
 Dizziness
 No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:
Special hazards:
Protective equipment for firefighters:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
 Can form explosive gas-air mixtures.
 A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:
Methods and material for containment and cleaning up:

Use respiratory protective device against the effects of fumes/dust/aerosol.
 Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling
Storage requirements:

Use only in well ventilated areas.
 Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm
 REL (USA) Long-term value: 1800 mg/m³, 1000 ppm
 TLV (USA) refer to Appendix F in TLVs and BEIs book

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm
 REL (USA) Long-term value: 590 mg/m³, 250 ppm
 TLV (USA) Short-term value: 1187 mg/m³, 500 ppm
 Long-term value: 594 mg/m³, 250 ppm
 BEI

8052-41-3 Stoddard Solvent

PEL (USA) Long-term value: 2900 mg/m³, 500 ppm
 REL (USA) Long-term value: 350 mg/m³
 Ceiling limit value: 1800* mg/m³
 *15-min
 TLV (USA) Long-term value: 525 mg/m³, 100 ppm

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm
 TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

110-19-0 isobutyl acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm
 REL (USA) Long-term value: 700 mg/m³, 150 ppm
 TLV (USA) Short-term value: NIC-712 mg/m³, NIC-150 ppm
 Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

110-54-3 hexane

PEL (USA) Long-term value: 1800 mg/m³, 500 ppm
 REL (USA) Long-term value: 180 mg/m³, 50 ppm
 TLV (USA) Long-term value: 176 mg/m³, 50 ppm
 Skin; BEI

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm
 REL (USA) Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV (USA) Short-term value: 651 mg/m³, 150 ppm
 Long-term value: 434 mg/m³, 100 ppm
 BEI

9006-04-6 RUBBER

TLV (USA) Long-term value: 0.0001* mg/m³
 Skin; DSEN, RSEN; * inh. fraction

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

(Contd. on page 3)

Safety Data Sheet

Printing date 02/08/2016

Revised On 02/08/2016

Trade name: TRUCK BED COATING

#708 Page 3 of 4

(Contd. of page 2)

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA) 50 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

110-54-3 hexane

BEI (USA) 0.4 mg/L
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: 2,5-Hexanedione without hydrolysis

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

Hygienic protection:

Immediately remove all soiled and contaminated clothing.
 Wash hands after use.
 Store protective clothing separately.
 Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Nitrile gloves.

Eye protection:

Protective gloves. The glove material must be impermeable and resistant to the substance.
 Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.
pH-value: Not determined.
Melting point/Melting range Undetermined.
Boiling point: -44 °C (-47 °F)
Flash point: -19 °C (-2 °F)
Flammability (solid, gas): Extremely flammable.
Decomposition temperature: Not determined.
Auto igniting: Product is not self-igniting.
Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: 1.0 Vol %
Upper Explosion Limit: 10.9 Vol %
Vapor pressure: Not determined.
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapour density Not determined.
Evaporation rate Not applicable.
Partition coefficient: n-octonal/water: Not determined.
Solubility: Not determined.
Viscosity: Not determined.
VOC content: 541.9 g/l / 4.52 lb/gl
VOC content (less exempt solvents): 63.2 %
Solids content: 22.1 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative LC50/4 h 658 mg/l (rat)

110-19-0 isobutyl acetate

Oral LD50 4763 mg/kg (rbt)

1330-20-7 xylene (mix)

Oral LD50 8700 mg/kg (rat)

Dermal LD50 2000 mg/kg (rbt)

(Contd. on page 4)

Safety Data Sheet

Trade name: TRUCK BED COATING

#708 Page 4 of 4

(Contd. of page 3)

Inhalative	LC50/4 h	6350 mg/l (rat)	
108-65-6 PM acetate			
Oral	LD50	8500 mg/kg (rat)	
Inhalative	LC50/4 h	35.7 mg/l (rat)	
Information on toxicological effects: No data available.			
Skin effects: No irritant effect.			
Eye effects: No irritating effect.			
Sensitization: No sensitizing effects known.			
Carcinogenic categories			
IARC (International Agency for Research on Cancer)			
1330-20-7	xylene (mix)		3
NTP (National Toxicology Program)			
None of the ingredients is listed.			

12 Ecological information

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.
Ecotoxicological effects:	
Remark:	Harmful to fish
Other adverse effects:	No further relevant information available.

13 Disposal considerations


Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number	UN1950
DOT	N/A
DOT	Consumer Commodity ORM-D
	Aerosols, flammable
	1950 Aerosols
ADR	
Transport hazard class(es):	
Class	2.1
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Packaging Group:	--
UN "Model Regulation":	UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):		
None of the ingredients in this product are listed.		
SARA Section 313 (Specific toxic chemical listings):		
110-54-3	hexane	
1330-20-7	xylene (mix)	
CPSC:	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.	
California Proposition 65 chemicals known to cause cancer:		
100-41-4	ethyl benzene	
1333-86-4	Carbon black	
CANADIAN ENVIRONMENTAL PROTECTION ACT:		
WHMIS Symbols for Canada:	All hazardous ingredients for this product appear on the Canadian Domestic Substance List. A - Compressed gas D2A - Very toxic material causing other toxic effects	
		
EPA:		
67-64-1	Acetone	I
110-19-0	isobutyl acetate	D
110-54-3	hexane	II
1330-20-7	xylene (mix)	I

16 Other information

Contact: Regulatory Affairs
Date of preparation / last revision 02/08/2016 / -