



## Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	28-1002-6	<b>Version Number:</b>	3.00
<b>Issue Date:</b>	08/29/16	<b>Supersedes Date:</b>	04/17/15

### Product identifier

3M™ Super-Fast Repair Adhesive PN 04747

### ID Number(s):

41-0003-6764-3, 60-4550-5242-7

### Recommended use

Automotive

### Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive Aftermarket
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

### Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:**

22-1807-1, 22-1870-9

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)





## Safety Data Sheet

Copyright, 2017, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	22-1807-1	<b>Version Number:</b>	7.01
<b>Issue Date:</b>	12/28/17	<b>Supersedes Date:</b>	08/29/16

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Super-Fast Repair Adhesive PN 04747 - Part A

#### Product Identification Numbers

LB-K100-0780-5, LA-D100-0021-7

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Two-part urethane system., Industrial use

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive Aftermarket
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

**Symbols**

Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Causes serious eye irritation.

Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure:  
respiratory system |

**Precautionary Statements****Prevention:**

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

In case of inadequate ventilation wear respiratory protection.

Wear eye/face protection.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Get medical advice/attention if you feel unwell.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

39% of the mixture consists of ingredients of unknown acute oral toxicity.

39% of the mixture consists of ingredients of unknown acute dermal toxicity.

41% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	25 - 60 Trade Secret *
Castor Oil, Polymer With 1,1'-Methylenebis[4-Isocyanatobenzene]	68424-09-9	15 - 40 Trade Secret *
4,4'-Diisocyanatodiphenylmethane Polymer	25686-28-6	5 - 25 Trade Secret *
3-(Trimethoxysilyl)Propyl Glycidyl Ether	2530-83-8	1 - 5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide

Carbon dioxide

Hydrogen Cyanide

Oxides of Nitrogen

Toxic Vapor, Gas, Particulate

**Condition**

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

**5.3. Special protective actions for fire-fighters**

No special protective actions for fire-fighters are anticipated.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from strong bases.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	ACGIH	TWA:0.005 ppm	
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	OSHA	CEIL:0.2 mg/m <sup>3</sup> (0.02 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Viscous
<b>Odor, Color, Grade:</b>	Low or no detectable odor, clear.
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	>=400 °F
<b>Flash Point</b>	>=290 °F [ <i>Test Method:</i> Tagliabue Closed Cup]
<b>Evaporation rate</b>	<=1 [ <i>Details:</i> Gels with exposure to humidity.]
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>Not Applicable</i>
<b>Flammable Limits(UEL)</b>	<i>Not Applicable</i>
<b>Vapor Pressure</b>	<=0.000004 mmHg [@ 68 °F]
<b>Vapor Density</b>	>=1 [ <i>Ref Std:</i> AIR=1]

Density	1.1 g/ml
Specific Gravity	1.1 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	Not Applicable
Decomposition temperature	No Data Available
Viscosity	1,000 - 2,000 centipoise
Hazardous Air Pollutants	42.133 lb HAPS/lb solids
Molecular weight	No Data Available
Volatile Organic Compounds	22 g/l [Test Method:calculated SCAQMD rule 443.1]
Volatile Organic Compounds	2.0 % weight [Test Method:calculated per CARB title 2]
Percent volatile	2.0 % weight [Test Method:Estimated]
VOC Less H2O & Exempt Solvents	22 g/l [Test Method:calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Water  
Strong acids  
Strong bases

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure



**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

**Skin Contact:**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Additional Health Effects:**

**Prolonged or repeated exposure may cause target organ effects:**

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

**Additional Information:**

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE <sub>20</sub> - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
P,P'-Methylenebis(Phenyl Isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
P,P'-Methylenebis(Phenyl Isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg
4,4'-Diisocyanatodiphenylmethane Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-Diisocyanatodiphenylmethane Polymer	Ingestion	Rat	LD50 31,600 mg/kg
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Dermal	Rabbit	LD50 4,000 mg/kg
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Ingestion	Rat	LD50 7,010 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	official classification	Irritant
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Irritant
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Rabbit	Mild irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	official classification	Severe irritant
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Severe irritant
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Rabbit	Corrosive

**Skin Sensitization**

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	official classification	Sensitizing
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Sensitizing
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Guinea pig	Not classified

**Respiratory Sensitization**

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	Human	Sensitizing
4,4'-Diisocyanatodiphenylmethane Polymer	Human	Sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
P,P'-Methylenebis(Phenyl Isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-Diisocyanatodiphenylmethane Polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
3-(Trimethoxysilyl)Propyl Glycidyl Ether	In vivo	Not mutagenic
3-(Trimethoxysilyl)Propyl Glycidyl Ether	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Dermal	Mouse	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure
------	-------	-------	---------	-------------	----------

					<b>Duration</b>
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
3-(Trimethoxysilyl)Propyl Glycidyl Ether	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### EPCRA 311/312 Hazard Classifications:

##### Physical Hazards

Not applicable

##### Health Hazards

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

#### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Trade Secret 25 - 60
P,P'-Methylenebis(Phenyl Isocyanate) (Benzene, 1,1'-methylenebis[4-isocyanato-)	101-68-8	25 - 60
P,P'-Methylenebis(Phenyl Isocyanate) (DIISOCYANATES (CERTAIN CHEMICALS ONLY))	101-68-8	25 - 60

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health: 2 Flammability: 1 Instability: 1 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health: \*2 Flammability: 1 Physical Hazard: 1 Personal Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

<b>Document Group:</b>	22-1807-1	<b>Version Number:</b>	7.01
<b>Issue Date:</b>	12/28/17	<b>Supersedes Date:</b>	08/29/16

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**



## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	22-1870-9	<b>Version Number:</b>	4.02
<b>Issue Date:</b>	01/30/18	<b>Supersedes Date:</b>	08/11/14

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Super Fast Adhesive PN 04747 Accelerator (Part B)

#### Product Identification Numbers

LB-K100-0780-6, LA-D100-0023-3

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Two-part urethane system., Industrial use

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive Aftermarket
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark |

**Pictograms****Hazard Statements**

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

**Precautionary Statements****General:**

Keep out of reach of children.

**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

18% of the mixture consists of ingredients of unknown acute inhalation toxicity.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Polyether Polyol	9082-00-2	40 - 70 Trade Secret *
Propoxylated Trimethylolpropane	25723-16-4	10 - 30 Trade Secret *
Tetrakis(2-Hydroxypropyl)Ethylenediamine	102-60-3	10 - 30 Trade Secret *
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	1 - 5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

In case of fire: Use a dry chemical extinguisher to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

**Substance**

Carbon monoxide  
Carbon dioxide  
Oxides of Nitrogen

**Condition**

During Combustion  
During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

No special protective actions for fire-fighters are anticipated.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.



**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid breathing of dust created by cutting, sanding, grinding or machining. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store away from acids. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
M-Xylene-Alpha,Alpha'-Diamine	1477-55-0	ACGIH	CEIL:0.1 mg/m3	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber Fluoroelastomer

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an

exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

### Respiratory protection

In case of inadequate ventilation wear respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure: Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Gel
Odor, Color, Grade:	Slight ammonia like odor, clear.
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>No Data Available</i>
Boiling Point	>=400 °F
Flash Point	>=290 °F [ <i>Test Method</i> :Tagliabue Closed Cup]
Evaporation rate	<=1 [ <i>Ref Std</i> :WATER=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Vapor Density	>=1 [ <i>Ref Std</i> :AIR=1]
Density	1.02 g/ml
Specific Gravity	1.02 [ <i>Ref Std</i> :WATER=1]
Solubility in Water	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	1,300 - 2,000 centipoise
Hazardous Air Pollutants	0 lb HAPS/lb solids [ <i>Test Method</i> :Calculated]
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	0 % weight [ <i>Test Method</i> :calculated per CARB title 2]
Volatile Organic Compounds	0 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]
Percent volatile	<=1 % weight [ <i>Test Method</i> :Estimated]
VOC Less H2O & Exempt Solvents	0 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

None known.

**10.5. Incompatible materials**

Strong acids

Strong oxidizing agents

**10.6. Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin Contact:**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion:**

No known health effects.

**Additional Information:**

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4)		No data available; calculated ATE >12.5 mg/l

	hr)		
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polyether Polyol	Dermal	Rabbit	LD50 > 5,000 mg/kg
Polyether Polyol	Ingestion	Rat	LD50 > 10,000 mg/kg
Propoxylated Trimethylolpropane	Dermal	Rat	LD50 > 2,000 mg/kg
Propoxylated Trimethylolpropane	Ingestion	Rat	LD50 > 2,500 mg/kg
Tetrakis(2-Hydroxypropyl)Ethylenediamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
Tetrakis(2-Hydroxypropyl)Ethylenediamine	Ingestion	Rat	LD50 3,280 mg/kg
M-Xylene-Alpha,Alpha'-Diamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
M-Xylene-Alpha,Alpha'-Diamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.2 mg/l
M-Xylene-Alpha,Alpha'-Diamine	Ingestion	Rat	LD50 980 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Propoxylated Trimethylolpropane	Rabbit	No significant irritation
M-Xylene-Alpha,Alpha'-Diamine	Rat	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
Propoxylated Trimethylolpropane	Rabbit	Mild irritant
M-Xylene-Alpha,Alpha'-Diamine	Rabbit	Corrosive

**Skin Sensitization**

Name	Species	Value
M-Xylene-Alpha,Alpha'-Diamine	Guinea pig	Sensitizing

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
M-Xylene-Alpha,Alpha'-Diamine	In Vitro	Not mutagenic
M-Xylene-Alpha,Alpha'-Diamine	In vivo	Not mutagenic

**Carcinogenicity**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
M-Xylene-Alpha,Alpha'-Diamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 450 mg/kg/day	1 generation
M-Xylene-Alpha,Alpha'-Diamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 450 mg/kg	1 generation
M-Xylene-Alpha,Alpha'-Diamine	Ingestion	Not classified for development	Rat	NOAEL 450 mg/kg/day	1 generation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
------	-------	-----------------	-------	---------	-------------	----------

						Duration
M-Xylene-Alpha,Alpha'-Diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
M-Xylene-Alpha,Alpha'-Diamine	Ingestion	endocrine system   blood   bone marrow	Not classified	Rat	NOAEL 600 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

**Physical Hazards**

Not applicable

**Health Hazards**

Serious eye damage or eye irritation

Skin Corrosion or Irritation

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: Other information**

**NFPA Hazard Classification**

**Health: 2 Flammability: 1 Instability: 1 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**HMIS Hazard Classification**

**Health: 2 Flammability: 1 Physical Hazard: 1 Personal Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

**Document Group:** 22-1870-9 **Version Number:** 4.02  
**Issue Date:** 01/30/18 **Supersedes Date:** 08/11/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**