

SAFETY DATA SHEET.

Issuing date 10-Aug-2017

Revision Date 10-Aug-2017

Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product identifier****Product name** 79A Aero-Ayd Rust Penetrant**Recommended use of the chemical and restrictions on use****Product code** F03686**Product Type** Extremely Flammable Aerosol
Synonyms None**Supplier's details****Recommended Use** Rust Removal.
Uses advised against No information available**Manufactured For:**
1st Ayd Corporation
1325 Gateway Drive
Elgin, IL 60124**Emergency telephone number**
Chemical Emergency Phone 800-255-3924
Number

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Harmful if inhaled
 Causes skin irritation
 May be fatal if swallowed and enters airways
 Extremely Flammable Aerosol
 Contains gas under pressure; may explode if heated



Appearance Slightly Hazy

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves
 Keep away from heat/sparks/open flames/hot surfaces.-No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

Specific treatment (see first aid on this label)
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse
 IF INHALED : Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor/physician
 IF SWALLOWED: Immediately call a poison center/doctor
 Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

F03686 - 79A AERO-AYD RUST PENETRANT

Revision Date 10-Aug-2017

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
HYDROTREATED LIGHT DISTILLATES	64742-47-8	20-30
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
NAPHTHENIC OIL, SEVERELY HYDROTREATED	64742-52-5	10-20
KEROSENE	8008-20-6	10-20
PETROLEUM DISTILLATES	64742-47-8	10-20
2-BUTOXYETHANOL	111-76-2	1-10
NaphthalenesulfonicAcid,CaSalt	57855-77-3	1-10
ETHYLENE GLYCOL	107-21-1	<0.1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURESFirst aid measures for different exposure routes

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors , mist, or gas.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. Seek immediate medical attention/advice. If eye irritation persists, consult a doctor.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms	Harmful if inhaled. May be fatal if swallowed and enters airways. May cause eye, skin, and respiratory irritation. Harmful if swallowed and enters the lungs.
----------------------	---

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURESSuitable Extinguishing Media

Water fog.Dry chemical. Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the occupational exposure limits.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Absorb with sand, clay, or other suitable material. hard surfaces may be mopped with water. Dam up. Cover liquid spill with sand, earth, or other noncombustible absorbent material. Take up mechanically and collect in suitable container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep containers tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on hot surfaces. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkali, or oxidizing agents.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH

F03686 - 79A AERO-AYD RUST PENETRANT

Revision Date 10-Aug-2017

HYDROTREATED LIGHT DISTILLATES 64742-47-8	TWA: 200 PPM 8 hours	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8: TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5: TWA: 800 ppm TWA: 1900 mg/m ³
KEROSENE 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures Skin - potential significant contribution to overall exposure by the cutaneous route	-	TWA: 100 mg/m ³
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
ETHYLENE GLYCOL 107-21-1	Ceiling: 100 mg/m ³ aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls**Engineering Measures**Showers
Eyewash stations
Ventilation systems.**Individual protection measures, such as personal protective equipment****Eye/Face Protection**

Safety glasses with side-shields.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Physical and chemical properties****Physical state**
Appearance
ColorAerosol
Slightly Hazy
Amber**Odor**
Odor Threshold

Solvent

Property**pH**
Melting/freezing point**Values**
No information available
No information available**Remarks • Methods**

Boiling point/boiling range		
Flash Point	-96.4 °C / -141 °F	Based on propellant
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit		
lower flammability limit		
Vapor pressure		
Vapor density		
Specific Gravity	0.785	
Water solubility	None	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	Not applicable
Decomposition temperature		
Viscosity	No information available	
Explosive properties		

Other information

VOC Content(%) 49.64

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkali , or oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Fumes, Hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	Harmful if inhaled. May cause respiratory irritation.
Eye contact	May cause eye irritation.
Skin contact	Causes skin irritation.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HYDROTREATED LIGHT DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h

PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	=31mg/L (Rat) 4 hr
KEROSENE 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
PETROLEUM DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
ETHYLENE GLYCOL 107-21-1	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)	-

Information on toxicological effects

Symptoms Harmful if inhaled. Causes skin irritation .May cause eye and respiratory irritation. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.
Eye damage/irritation May cause eye irritation.
Irritation May cause skin, eye, and respiratory irritation.
Sensitization No information available.
Germ Cell Mutagenicity Not a germ cell mutagen.
Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-BUTOXYETHANOL 111-76-2	-	Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

Reproductive toxicity This product does not contain any known or suspected reproductive hazards.

Specific target organ systemic toxicity (single exposure) No information available.

Specific target organ systemic toxicity (repeated exposure) No information available.

Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

Target Organ Effects Eyes, Skin, Respiratory System, Central Nervous System, Liver, Kidney, and Lungs.
Neurological effects Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 3165 mg/kg
ATEmix (dermal) 12362 mg/kg
ATEmix (inhalation-gas) 198334 mg/l
ATEmix (inhalation-dust/mist) 16.9 mg/l
ATEmix (inhalation-vapor) 379 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
HYDROTREATED LIGHT DISTILLATES 64742-47-8	-	45 mg/L LC50 Pimephales promelas 96h flow-through 2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-
NAPHTHENIC OIL, SEVERELY HYDROTREATED 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
PETROLEUM DISTILLATES 64742-47-8	-	45 mg/L LC50 Pimephales promelas 96h flow-through 2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static	-	-
2-BUTOXYETHANOL 111-76-2	-	1490 mg/L LC50 Lepomis macrochirus 96h static 2950 mg/L LC50 Lepomis macrochirus 96h	-	1000 mg/L EC50 Daphnia magna 48h
ETHYLENE GLYCOL 107-21-1	6500 - 13000 mg/L EC50 Pseudokirchneriella subcapitata 96h	41000 mg/L LC50 Oncorhynchus mykiss 96h 14 - 18 mL/L LC50 Oncorhynchus mykiss 96h static 27540 mg/L LC50 Lepomis macrochirus 96h static 40761 mg/L LC50 Oncorhynchus mykiss 96h static 40000 - 60000 mg/L LC50 Pimephales promelas 96h static 16000 mg/L LC50 Poecilia reticulata 96h static	-	46300 mg/L EC50 Daphnia magna 48h

Persistence and degradability

.

Bioaccumulation

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	<=2.8
2-BUTOXYETHANOL 111-76-2	0.81
ETHYLENE GLYCOL 107-21-1	-1.93

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment****Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION**International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HYDROTREATED LIGHT DISTILLATES	X	X	X	Not listed	X	X	X	X
PROPANE/ISOBUTA NE/N-BUTANE	X	X	X	x	X	X	X	X
NAPHTHENIC OIL, SEVERELY HYDROTREATED	X	X	X	Not listed	X	X	X	X
KEROSENE	X	X	X	x	X	X	X	X
PETROLEUM DISTILLATES	X	X	X	x	X	X	X	X
2-BUTOXYETHANOL	X	X	X	X	X	X	X	X
NaphthalenesulfonicAc id,CaSalt	X	X	X	X	X	X	X	X
ETHYLENE GLYCOL	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
CHINA - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
2-BUTOXYETHANOL - 111-76-2	111-76-2	1-10	1.0

ETHYLENE GLYCOL - 107-21-1	107-21-1	<0.1	1.0
NAPHTHALENE - 91-20-3	91-20-3	<0.1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ETHYLENE GLYCOL 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
ETHYLENE GLYCOL - 107-21-1	Developmental
NAPHTHALENE - 91-20-3	Cancer

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KEROSENE 8008-20-6	X	X	X
2-BUTOXYETHANOL 111-76-2	X	X	X
ETHYLENE GLYCOL 107-21-1	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B
<i>Chronic Hazard Star Legend</i>	<i>Chronic Health Star Hazard Repeated or prolonged exposure may cause central nervous system damage</i>			

Prepared By American Jetway
34136 Myrtle Street
Wayne, MI 48184
Tel.734-721-5930

Issuing date 10-Aug-2017
Revision Date 10-Aug-2017

Revision Note
(M)SDS sections updated

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet