# SAFETY DATA SHEET

#81 PAGE 1 OF 9

1. Identification

Product identifier **Gunk Engine Cleaner - Foamy** 

Other means of identification

SDS number FEB1 Part No. FEB1

Tariff code 3402.20.5100 Recommended use Engine Cleaner Recommended restrictions

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name **RSC Chemical Solutions** Address 600 Radiator Road

Indian Trail, NC 28079

**United States** Telephone Customer Service:

(704) 821-7643 Technical: (704) 684-1811

Website www.rscbrands.com

E-mail Not available.

**Emergency phone number** Emergency Telephone: (303) 623-5716

None known.

**Emergency Contact:** RMPDC (877-740-5015)

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 2 Health hazards Germ cell mutagenicity Category 1B Carcinogenicity Category 1A

**Environmental hazards** Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements





Signal word

Hazard statement Flammable aerosol. May cause genetic defects. May cause cancer. Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid release to the environment. Wear protective gloves/protective clothing/eye

Category 3

protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise None known.

classified (HNOC)

Supplemental information

16.4% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 15.46% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

# 3. Composition/information on ingredients

#### Mixtures

Chemical name Common name and synony		CAS number	%	
Petroleum Gases, Liquefied, Sweetened; Petroleum Gas;		68476-86-8	5 - < 10	
Kerosine (petroleum)		8008-20-6	1 - < 3	
Nonylphenolethoxylate		9016-45-9	1 - < 3	
Petroleum naphtha		64742-94-5	1 - < 3	
NAPHTHALENE		91-20-3	< 0.2	
Other components below reportable levels	S		80 - < 90	

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation

If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

In the unlikely event of swallowing contact a physician or poison control center.

Most important

symptoms/effects, acute and

delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

treatment needed General information Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions During fire, gases hazardous to health may be formed. Firefighters must use standard protective equipment including flame retardant coat, helmet with

face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Containers should be cooled with

water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Specific methods

Flammable aerosol.

# 6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

Value

### 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.1000)
Componente	Tyne

rype	value	
PEL	50 mg/m3	
	10 ppm	
PEL	400 mg/m3	
	100 ppm	
Туре	Value	Form
TWA	200 mg/m3	Non-aerosol.
TWA	10 ppm	
TWA	200 mg/m3	Non-aerosol.
ical Hazards		
Type	Value	
TWA	100 mg/m3	
STEL	75 mg/m3	
	15 ppm	
TWA	50 mg/m3	
	PEL PEL Type TWA TWA TWA ical Hazards Type TWA STEL	PEL 50 mg/m3  10 ppm 400 mg/m3 100 ppm  Type Value  TWA 200 mg/m3  TWA 10 ppm  TWA 200 mg/m3  TWA 200 mg/m3  TWA 200 mg/m3  TWA 10 ppm  TWA 200 mg/m3  Ical Hazards Type Value  TWA 100 mg/m3  STEL 75 mg/m3  15 ppm

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines** 

US ACGIH Threshold Limit Values: Skin designation

Kerosine (petroleum) (CAS 8008-20-6) NAPHTHALENE (CAS 91-20-3) Can be absorbed through the skin. Can be absorbed through the skin.

10 ppm

Petroleum naphtha (CAS 64742-94-5)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

Appearance Liquid. Hazy
Physical state Liquid.

Form Aerosol.
Color Cream

Odor Sweet. Aromatic.
Odor threshold Not available.

**pH** 9 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point > 201.0 °F (> 93.9 °C) Tag Closed Cup

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

oppositioner maininability of explosiv

Flammability limit - lower (%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.
Explosive limit - upper (%) Not available.

Vapor pressure 0.00001 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 8.17 lbs/gal
Explosive properties Not explosive.

Flame extension 0 in Flammability (flash back) No

Flammability class

Combustible IIIB estimated

Heat of combustion (NFPA

30B)

Oxidizing properties

Not oxidizing.

Percent volatile

82.26 % estimated

2.36 kJ/g estimated

Specific gravity

0.85

VOC (Weight %)

1.83 % estimated

### 10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

No hazardous decomposition products are known.

products

# 11. Toxicological information

Information on likely routes of exposure

Inhalation

Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected. Direct contact with eyes may cause temporary irritation.

Eye contact Ingestion

Expected to be a low ingestion hazard.

Symptoms related to the

Direct contact with eyes may cause temporary irritation.

physical, chemical and toxicological characteristics

### Information on toxicological effects

Acute toxicity

Components	Species	Test Results
NAPHTHALENE (CAS 91-2	20-3)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2 g/kg
	Rat	> 20 g/kg
Oral		
LD50	Guinea pig	1200 mg/kg
	Rat	490 mg/kg
Petroleum naphtha (CAS 6	4742-94-5)	
<u>Acute</u>		
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
Oral		
LD50	Rat	> 25 ml/kg

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Direct contact with eyes may cause temporary irritation.

#### Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

May cause genetic defects.

Material name: Gunk Engine Cleaner - Foamy FEB1 Version #: 01 Issue date: 05-29-2015 Carcinogenicity

May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

NAPHTHALENE (CAS 91-20-3)

2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

US. National Toxicology Program (NTP) Report on Carcinogens

NAPHTHALENE (CAS 91-20-3)

Reasonably Anticipated to be a Human Carcinogen.

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Reproductive toxicity

Specific target organ toxicity -

Not classified.

repeated exposure

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

# 12. Ecological information

**Ecotoxicity** 

Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
NAPHTHALENE (CAS	S 91-20-3)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha)	1.11 - 1.68 mg/l, 96 hours
Nonylphenolethoxylate	e (CAS 9016-45-9)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	12.2 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	1 - 1.8 mg/l, 96 hours
Petroleum naphtha (C	AS 64742-94-5)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

NAPHTHALENE

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

3.3

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

#### #81 PAGE 7 OF 9

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

# 14. Transport information

DOT

**UN** number Not available.

UN proper shipping name

Transport hazard class(es)

Class ORM-D Subsidiary risk None Label(s)

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Consumer commodity

Packaging exceptions 156, 306 156, 306 Packaging non bulk None Packaging bulk

IATA

UN number ID8000

UN proper shipping name Consumer commodity

Transport hazard class(es)

Class Subsidiary risk

Packing group Not applicable.

Environmental hazards No. **ERG Code** 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Cargo aircraft only Allowed.

Allowed.

Not established.

IMDG

UN1950 **UN** number Aerosols UN proper shipping name

Transport hazard class(es)

Class 2 Subsidiary risk

Not applicable. Packing group

**Environmental hazards** 


Marine pollutant No. F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

**IATA** 



Material name: Gunk Engine Cleaner - Foamy FEB1 Version #: 01 Issue date: 05-29-2015

#81 PAGE 8 OF 9 IMDG



### 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans, Chemicals of Concern

Nonylphenolethoxylate (CAS 9016-45-9)

Nonylphenol (NP) and Nonylphenol Ethoxylates (NPEs) Action

Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

NAPHTHALENE (CAS 91-20-3) SARA 304 Emergency release notification Listed. Listed.

Nonylphenolethoxylate (CAS 9016-45-9)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Nonylphenolethoxylate	9016-45-9	1 - < 3	_
NAPHTHALENE	91-20-3	< 0.2	

### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

### US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Kerosine (petroleum) (CAS 8008-20-6)

NAPHTHALENE (CAS 91-20-3)

Nonylphenolethoxylate (CAS 9016-45-9)

Petroleum Gases, Liquefied, Sweetened; Petroleum Gas; (CAS 68476-86-8)

Petroleum naphtha (CAS 64742-94-5)

#### #81 PAGE 9 OF 9

#### US. Massachusetts RTK - Substance List

Kerosine (petroleum) (CAS 8008-20-6)

# NAPHTHALENE (CAS 91-20-3)

# US. New Jersey Worker and Community Right-to-Know Act

Kerosine (petroleum) (CAS 8008-20-6) NAPHTHALENE (CAS 91-20-3) Nonylphenolethoxylate (CAS 9016-45-9) Petroleum naphtha (CAS 64742-94-5)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Kerosine (petroleum) (CAS 8008-20-6) NAPHTHALENE (CAS 91-20-3) Nonylphenolethoxylate (CAS 9016-45-9)

#### US. Rhode Island RTK

NAPHTHALENE (CAS 91-20-3)

Nonylphenolethoxylate (CAS 9016-45-9)

#### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

# US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

DIETHANOLAMINE (CAS 111-42-2) NAPHTHALENE (CAS 91-20-3)

Listed: June 22, 2012 Listed: April 19, 2002

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

05-29-2015 Issue date

Version #

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge.

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.