

**Safety Data Sheet  
VOC Tar/Adhesive Remover**

Version 1.0

Revision Date: 06/18/2015

---

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name** : VOC Tar/Adhesive Remover  
**Product Use Description** : Blanket Roller Wash

**Manufacturer or supplier's details**

**Company** : Nexeo Solutions LLC  
**Address** : 3 Waterway Square Place Suite 1000  
Woodlands, Tx. 77380  
United States of America

**Emergency telephone number:**

Health North America: 1-855-NEXEO4U (1-855-639-3648)

Health International: 1-855-NEXEO4U (1-855-639-3648)

Transport North America: CHEMTREC 800.424.9300

**Additional Information:** : Responsible Party: Product Safety Group  
E-Mail: msds@nexeosolutions.com  
SDS Requests: 1-855-429-2661  
SDS Requests Fax: 1-281-500-2370  
Website: www.nexeosolutions.com

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2 (Liver, Kidney, Central nervous system)

Specific target organ toxicity - repeated exposure (Oral) : Category 2

Aspiration hazard : Category 1

**GHS Label element**

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

Hazard pictograms



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.  
H373 May cause damage to organs (Liver, Kidney, Central nervous system) through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 Get medical advice/ attention if you feel unwell.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

## Potential Health Effects

### Carcinogenicity:

#### IARC

Group 2B: Possibly carcinogenic to humans

100-41-4

\*\*Ethylbenzene

91-20-3

\*\*Naphthalene

98-82-8

\*\*Cumene

#### ACGIH

Confirmed animal carcinogen with unknown relevance to humans

100-41-4

\*\*Ethylbenzene

#### OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### NTP

Reasonably anticipated to be a human carcinogen

91-20-3

\*\*Naphthalene

## Emergency Overview

Appearance	liquid
Colour	clear, colourless
Hazard Summary	No information available.

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

Substance / Mixture : Mixture

### Hazardous components

CAS-No.	Chemical Name	Concentration (%)
64742-47-8	Distillates (pet), hydrotreated light	50 - 70
1330-20-7	Mixed xylenes	10 - 20
64742-94-5	Solvent naphtha (petroleum), heavy arom.	10 - 20
98-06-6	**Butylbenzene, tert-	5 - 10
100-41-4	**Ethylbenzene	5 - 10
527-53-7	**Benzene, 1,2,3,5-tetramethyl-	1 - 5
95-93-2	**Benzene, 1,2,4,5-tetramethyl-	1 - 5
105-05-5	**1,4-Diethylbenzene	1 - 5
488-23-3	**1,2,3,4-Tetramethylbenzene	1 - 5
91-20-3	**Naphthalene	1 - 5
526-73-8	**Benzene, 1,2,5-trimethyl-	1 - 5
1074-43-7	**3-Propyltoluene	1 - 5
95-63-6	**1,2,4-trimethylbenzene	1 - 5
98-82-8	**Cumene	0.1 - 1

**Special Notes:** : \*\* Other substances in the product which may present a health or environmental hazard.

### SECTION 4. FIRST AID MEASURES

- General advice** : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled** : Consult a physician after significant exposure.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact** : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact** : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed** : Keep respiratory tract clear.  
Do NOT induce vomiting.

## **Safety Data Sheet**

### **VOC Tar/Adhesive Remover**

Version 1.0

Revision Date: 06/18/2015

Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### **SECTION 5. FIREFIGHTING MEASURES**

- |   |  |
|---|--|
| Suitable extinguishing media                  | : Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical<br>Water spray   |
| Unsuitable extinguishing media                | : High volume water jet  |
| Specific hazards during firefighting          | : Do not allow run-off from fire fighting to enter drains or water courses.  |
| Hazardous combustion products                 | : No hazardous combustion products are known   |
| Specific extinguishing methods                | : Use a water spray to cool fully closed containers.   |
| Further information                           | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>For safety reasons in case of fire, cans should be stored separately in closed containments. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for fire-fighting if necessary.<br>Use personal protective equipment.  |

**NFPA Flammable and Combustible Liquids Classification:**  
Flammable Liquid Class IC

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

- |   |  |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Ensure adequate ventilation.<br>Remove all sources of ignition.<br>Evacuate personnel to safe areas.<br>Beware of vapours accumulating to form explosive |
|---|--|

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

Environmental precautions	<p>concentrations. Vapours can accumulate in low areas.</p> <p>: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.</p>
Methods and materials for containment and cleaning up	<p>: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).</p>

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	<p>: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.</p>
Conditions for safe storage	<p>: No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.</p>

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

CAS-No.	Components	Value type (Form of	Control parameters / Permissi-	Basis
---------	------------	------------------------	--------------------------------	-------

# **Safety Data Sheet** **VOC Tar/Adhesive Remover**

Version 1.0

Revision Date: 06/18/2015

		exposure)	ble concentra- tion	
64742-47-8	Distillates (pet), hy- drotreated light	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (as total hydro- carbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0
1330-20-7	Mixed xylenes	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	OSHA Z-1
64742-94-5	Solvent naphtha (petrole- um), heavy arom.	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (as total hydro- carbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
91-20-3	**Naphthalene	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm 50 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0
526-73-8	**Benzene, 1,2,5- trimethyl-	TWA	25 ppm 125 mg/m3	NIOSH REL
95-63-6	**1,2,4-trimethylbenzene	TWA	25 ppm 125 mg/m3	NIOSH REL
98-82-8	**Cumene	TWA	50 ppm	ACGIH
		TWA	50 ppm	NIOSH REL

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

			245 mg/m3	
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
**Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift at end of work-week	0.7 g/g creatinine	ACGIH BEI

### Personal protective equipment

- Respiratory protection : No personal respiratory protective equipment normally required.  
In the case of vapour formation use a respirator with an approved filter.
- Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : clear, colourless



## **Safety Data Sheet** **VOC Tar/Adhesive Remover**

Version 1.0

Revision Date: 06/18/2015

Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash point	: 27.2 °C (81.0 °F)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Burning rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.833 g/cm <sup>3</sup>
Bulk density	: No data available
Water solubility	: No data available
Solubility in other sol- vents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No dangerous reaction known under conditions of
------------	---

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

	normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No hazards to be specially mentioned.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: alkalis Chromic acid Strong acids Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	: None known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

##### Product:

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : 27022 ppm Exposure time: 4 h Test atmosphere: gas Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : 4,436 mg/kg Method: Calculation method

##### Components:

##### **64742-47-8:**

Acute oral toxicity	: LD50 (rat): > 5,000 mg/kg
Acute inhalation toxicity	: Remarks: No data available
Acute dermal toxicity	: LD50 (rabbit, male and female): > 2,000 mg/kg Method: Fixed dose procedure GLP: yes Assessment: The substance or mixture has no acute dermal toxicity

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

May be fatal if swallowed and enters airways.

### **1330-20-7:**

May be fatal if swallowed and enters airways.

### **64742-94-5:**

May be fatal if swallowed and enters airways.

## Further information

### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Components:**

##### **64742-47-8:**

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 25 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 1.4 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae	: EL50 (Pseudokirchneriella subcapitata (green algae)): 1 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 201 GLP: yes

### **Ecotoxicology Assessment**

Acute aquatic toxicity : Toxic to aquatic life.

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

Chronic aquatic toxicity	: Toxic to aquatic life with long lasting effects.
<b>1330-20-7:</b>	
Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 2.6 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1 mg/l Exposure time: 24 h Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata): 4.36 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 201 GLP: yes
Ecotoxicology Assessment	
Acute aquatic toxicity	: Toxic to aquatic life.
Chronic aquatic toxicity	: Toxic to aquatic life with long lasting effects.
<b>64742-94-5:</b>	
Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h Test Type: semi-static test Analytical monitoring: yes Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 1.4 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae	: EL50 (Pseudokirchneriella subcapitata (green algae)): 1 - 3 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

### Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

### Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

#### Components:

##### **64742-47-8:**

Biodegradability : aerobic  
Concentration: 101 mg/l  
Biodegradation: 61 %  
Exposure time: 28 d  
GLP: yes  
Remarks: Readily biodegradable

##### **1330-20-7:**

Biodegradability : Inoculum: activated sludge  
Result: Readily biodegradable.  
Biodegradation: 72 %  
Exposure time: 20 d

##### **64742-94-5:**

Biodegradability : aerobic  
Concentration: 2 mg/l  
Biodegradation: 30 %  
Exposure time: 28 d  
Test substance: Solvent naphtha (petroleum), heavy aromatic  
GLP: yes  
Remarks: Not readily biodegradable.

### Bioaccumulative potential

#### Components:

##### **1330-20-7:**

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

##### **64742-94-5:**

Partition coefficient: n-octanol/water : log Pow: 3.2 - 4.5

##### **91-20-3:**

Partition coefficient: n-octanol/water : log Pow: 3.4 (25 °C)

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

octanol/water

pH: 7 - 7.5

### 526-73-8:

Partition coefficient: n-octanol/water

: Remarks: No data available

### 95-63-6:

Partition coefficient: n-octanol/water

: Remarks: No data available

### 98-82-8:

Partition coefficient: n-octanol/water

: log Pow: 3.55 (23 °C)

### Mobility in soil

No data available

### Other adverse effects

No data available

### Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues

: Dispose of in accordance with all applicable local, state and federal regulations.  
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

Contaminated packaging

: Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

### SECTION 14. TRANSPORT INFORMATION

**IATA (International Air Transport Association):** UN1993, FLAMMABLE LIQUID, N.O.S., (PETROLEUM DISTILLATE, HYDROTREATED LIGHT, MIXED XYLENES) , 3, III, Flash Point:27.2 °C(81.0 °F)

**IMDG (International Maritime Dangerous Goods):** UN1993, FLAMMABLE LIQUID, N.O.S., (PETROLEUM DISTILLATE, HYDROTREATED LIGHT, MIXED XYLENES), 3, III, Marine Pollutant (PETROLEUM DISTILLATE, HYDROTREATED LIGHT, MIXED XYLENES)

**DOT (Department of Transportation):** UN1993, Flammable liquids, n.o.s., (PETROLEUM DISTILLATE, HYDROTREATED LIGHT, MIXED XYLENES), 3, III

### SECTION 15. REGULATORY INFORMATION

**OSHA Hazards** : Flammable liquid, Moderate skin irritant, Moderate eye irritant, Specific target organ toxicity - single exposure, Specific target organ toxicity - repeated exposure, Aspiration hazard

**WHMIS Classification** : B2: Flammable liquid  
D2A: Very Toxic Material Causing Other Toxic Effects  
D2B: Toxic Material Causing Other Toxic Effects

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Mixed xylenes	1330-20-7	100	526

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard  
Chronic Health Hazard

#### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

100-41-4	**Ethylbenzene	5.7 %
91-20-3	**Naphthalene	1.9 %
108-88-3	**Toluene	0.9499 %

## Safety Data Sheet VOC Tar/ Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

98-82-8	**Cumene	0.1994 %
71-43-2	**Benzene	0.0038 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F). The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7	Mixed xylenes	19 %
100-41-4	**Ethylbenzene	5.7 %
108-88-3	**Toluene	0.9499 %
98-82-8	**Cumene	0.1994 %
71-43-2	**Benzene	0.0038 %

### Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7	Mixed xylenes	19 %
100-41-4	**Ethylbenzene	5.7 %
91-20-3	**Naphthalene	1.9 %
108-88-3	**Toluene	0.9499 %
71-43-2	**Benzene	0.0038 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

1330-20-7	Mixed xylenes	19 %
100-41-4	**Ethylbenzene	5.7 %
91-20-3	**Naphthalene	1.9 %
108-88-3	**Toluene	0.9499 %
71-43-2	**Benzene	0.0038 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

100-41-4	**Ethylbenzene	5.7 %
91-20-3	**Naphthalene	1.9 %

### US State Regulations

#### Massachusetts Right To Know

1330-20-7	Mixed xylenes	10 - 20 %
98-06-6	**Butylbenzene, tert-	5 - 10 %
100-41-4	**Ethylbenzene	5 - 10 %
105-05-5	**1,4-Diethylbenzene	1 - 5 %
91-20-3	**Naphthalene	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %
71-43-2	**Benzene	0 - 0.1 %

#### Pennsylvania Right To Know

64742-47-8	Distillates (pet), hydrotreated light	50 - 70 %
1330-20-7	Mixed xylenes	10 - 20 %
64742-94-5	Solvent naphtha (petroleum), heavy arom.	10 - 20 %
98-06-6	**Butylbenzene, tert-	5 - 10 %
100-41-4	**Ethylbenzene	5 - 10 %



## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

527-53-7	**Benzene, 1,2,3,5-tetramethyl-	1 - 5 %
105-05-5	**1,4-Diethylbenzene	1 - 5 %
91-20-3	**Naphthalene	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %
108-88-3	**Toluene	0.1 - 1 %
98-82-8	**Cumene	0.1 - 1 %

### New Jersey Right To Know

64742-47-8	Distillates (pet), hydrotreated light	50 - 70 %
1330-20-7	Mixed xylenes	10 - 20 %
64742-94-5	Solvent naphtha (petroleum), heavy arom.	10 - 20 %
98-06-6	**Butylbenzene, tert-	5 - 10 %
100-41-4	**Ethylbenzene	5 - 10 %
91-20-3	**Naphthalene	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %
108-88-3	**Toluene	0.1 - 1 %

### California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.	
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene
98-82-8	**Cumene
71-43-2	**Benzene
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
108-88-3	**Toluene
71-43-2	**Benzene

### The components of this product are reported in the following inventories:

<b>United States TSCA Inventory</b>	:	y (positive listing) (On TSCA Inventory)
<b>Canadian Domestic Substances List (DSL)</b>	:	y (positive listing) (All components of this product are on the Canadian DSL.)
<b>Australia Inventory of Chemical Substances (AICS)</b>	:	y (positive listing) (On the inventory, or in compliance with the inventory)
<b>New Zealand. Inventory of Chemical Substances</b>	:	n (Negative listing) (Not in compliance with the inventory)

## Safety Data Sheet VOC Tar/Adhesive Remover


Version 1.0

Revision Date: 06/18/2015

<b>Japan. ENCS - Existing and New Chemical Substances Inventory</b>	:	n (Negative listing) (Not in compliance with the inventory)
<b>Korea. Korean Existing Chemicals Inventory (KECI)</b>	:	y (positive listing) (On the inventory, or in compliance with the inventory)
<b>Philippines Inventory of Chemicals and Chemical Substances (PICCS)</b>	:	y (positive listing) (On the inventory, or in compliance with the inventory)
<b>China. Inventory of Existing Chemical Substances in China (IECSC)</b>	:	y (positive listing) (On the inventory, or in compliance with the inventory)

### SECTION 16. OTHER INFORMATION **Further information**

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

## Safety Data Sheet VOC Tar/Adhesive Remover

Version 1.0

Revision Date: 06/18/2015

### Material number:

788497, 788412, 788411

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50			Lethal Concentration 50%