

# Safety Data Sheet

Printing date 03/17/2017

Revised On 03/10/2017

## 1 Identification of the substance and manufacturer

**Trade name:** DARK MACHINERY GRAY (ANSI 49)  
**Product code:** 0006201417  
**Product category:** PC9a Paints and coatings.  
**Manufacturer/Supplier:** Seymour of Sycamore  
 917 Crosby Avenue  
 Sycamore, IL 60178  
 phone: 815-895-9101  
 www.seymourpaint.com  
**Emergency telephone number:** CHEMTEL 1-800-255-3924, or 813-248-0585.

#MRO88DMG Page 1 of 5

## 2 Hazard(s) identification

### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.  
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

### GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

### Signal word

Danger

### Hazard statements

Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 May cause drowsiness or dizziness.

### Precautionary statements

May cause damage to organs through prolonged or repeated exposure.  
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a POISON CENTER/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Protect from sunlight. Store in a well-ventilated place.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

### Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

Component	Percentage
67-64-1 Acetone	18.88%
74-98-6 propane	15.74%
106-97-8 n-butane	9.25%
7727-43-7 barium sulfate	9.02%
110-19-0 Isobutyl Acetate	8.3%
2807-30-9 Glycol Ether EP	6.77%
13463-67-7 titanium dioxide	4.79%
123-86-4 n-butyl acetate	3.43%
107-87-9 Methyl Propyl Ketone	1.58%
108-10-1 methyl isobutyl ketone	1.1%

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.  
**After swallowing:** Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.  
**Most important symptoms and effects:** Dizziness  
**Indication of any immediate medical attention needed:** No further relevant information available.

## 5 Fire-fighting measures

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.

(Contd. on page 2)

## Safety Data Sheet

Printing date 03/17/2017

Revised On 03/10/2017

Trade name: DARK MACHINERY GRAY (ANSI 49)

#MRO88DMG Page 2 of 5

(Contd. of page 1)

**Special hazards:** Can form explosive gas-air mixtures.  
**Protective equipment for firefighters:** A respiratory protective device may be necessary.

**6 Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Wear protective equipment. Keep unprotected persons away.  
 Use respiratory protective device against the effects of fumes/dust/aerosol.  
**Methods and material for containment and cleaning up:** Ensure adequate ventilation.

**7 Handling and storage**

**Precautions for safe handling:** Use only in well ventilated areas.  
**Storage requirements:** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm  
 REL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm  
 TLV (USA) Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm  
 Long-term value: 594 mg/m<sup>3</sup>, 250 ppm  
 BEI

**74-98-6 propane**

PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm  
 REL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm  
 TLV (USA) refer to Appendix F in TLVs&BEIs book; NIC-EX

**106-97-8 n-butane**

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm  
 TLV (USA) Short-term value: (2370) mg/m<sup>3</sup>, (1000) ppm  
 NIC-EX

**7727-43-7 barium sulfate**

PEL (USA) Long-term value: 15\* 5\*\* mg/m<sup>3</sup>  
 \*total dust \*\*respirable fraction  
 REL (USA) Long-term value: 10\* 5\*\* mg/m<sup>3</sup>  
 \*total dust \*\*respirable fraction  
 TLV (USA) Long-term value: 5\* mg/m<sup>3</sup>  
 \*inhalable fraction; E

**110-19-0 Isobutyl Acetate**

PEL (USA) Long-term value: 700 mg/m<sup>3</sup>, 150 ppm  
 REL (USA) Long-term value: 700 mg/m<sup>3</sup>, 150 ppm  
 TLV (USA) Short-term value: 172 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

**123-86-4 n-butyl acetate**

PEL (USA) Long-term value: 710 mg/m<sup>3</sup>, 150 ppm  
 REL (USA) Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
 Long-term value: 710 mg/m<sup>3</sup>, 150 ppm  
 TLV (USA) Short-term value: 712 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

**107-87-9 Methyl Propyl Ketone**

PEL (USA) Long-term value: 700 mg/m<sup>3</sup>, 200 ppm  
 REL (USA) Long-term value: 530 mg/m<sup>3</sup>, 150 ppm  
 TLV (USA) Short-term value: 529 mg/m<sup>3</sup>, 150 ppm

**108-10-1 methyl isobutyl ketone**

PEL (USA) Long-term value: 410 mg/m<sup>3</sup>, 100 ppm  
 REL (USA) Short-term value: 300 mg/m<sup>3</sup>, 75 ppm  
 Long-term value: 205 mg/m<sup>3</sup>, 50 ppm  
 TLV (USA) Short-term value: 307 mg/m<sup>3</sup>, 75 ppm  
 Long-term value: 82 mg/m<sup>3</sup>, 20 ppm  
 BEI

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA) 50 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Acetone (nonspecific)

(Contd. on page 3)

## Safety Data Sheet

Printing date 03/17/2017

Revised On 03/10/2017

Trade name: DARK MACHINERY GRAY (ANSI 49)

#MRO88DMG Page 3 of 5

(Contd. of page 2)

**108-10-1 methyl isobutyl ketone**

BEI (USA) 1 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: MIBK

**Hygienic protection:** Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:** Nitrile gloves.  
Protective gloves. The glove material must be impermeable and resistant to the substance.

**Eye protection:** Tightly sealed goggles

**9 Physical and chemical properties**

**Appearance:** Aerosol.  
**Odor:** Aromatic  
**Odor threshold:** Not determined.  
**pH-value:** Not determined.  
**Melting point/Melting range** Undetermined.  
**Boiling point:** -44 °C (-47 °F)  
**Flash point:** -19 °C (-2 °F)  
**Flammability (solid, gas):** Extremely flammable.  
**Decomposition temperature:** Not determined.  
**Auto igniting:** Product is not self-igniting.  
**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.  
**Lower Explosion Limit:** 1.7 Vol %  
**Upper Explosion Limit:** 10.9 Vol %  
**Vapor pressure:** Not determined.  
**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)  
**Vapor density** Not determined.  
**Evaporation rate** Not applicable.  
**Partition coefficient: n-octanol/water:** Not determined.  
**Solubility:** Not determined.  
**Viscosity:** Not determined.  
**VOC content (less exempt solvents):** 47.7 %  
**Solids content:** 32.9 %

**10 Stability and reactivity**

**Reactivity:** Stable at normal temperatures.  
**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.  
**Chemical stability:** Not fully evaluated.  
**Possibility of hazardous reactions:** No dangerous reactions known.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

**11 Toxicological information****LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

**110-19-0 Isobutyl Acetate**

Oral	LD50	4763 mg/kg (rbt)
------	------	------------------

**13463-67-7 titanium dioxide**

Oral	LD50	>20000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rbt)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

**123-86-4 n-butyl acetate**

Oral	LD50	14000 mg/kg (rat)
Inhalative	LC50/4 h	>21.0 mg/l (rat)

**108-10-1 methyl isobutyl ketone**

Oral	LD50	2100 mg/kg (rat)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

**Information on toxicological effects:** No data available.**Skin effects:** No irritant effect.**Eye effects:** Irritating effect.

(Contd. on page 4)

**Safety Data Sheet**

Printing date 03/17/2017

Revised On 03/10/2017

Trade name: DARK MACHINERY GRAY (ANSI 49)

#MRO88DMG Page 4 of 5

**Sensitization:** No sensitizing effects known.

(Contd. of page 3)

**12 Ecological information**

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.

**14 Transport information**

**UN-Number:** UN1950  
**DOT:** N/A  
**DOT:** Consumer Commodity ORM-D  
**ADR:** Aerosols, flammable  
**ADR:** 1950 Aerosols  
**Transport hazard class(es):**  
**Class:** 2.1  
**Marine pollutant:** No  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**Stowage Code:** SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
**Segregation Code:** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.  
**Quantity limitations:** On passenger aircraft/rail: 75 kg  
On cargo aircraft only: 150 kg  


---

**ADR:**  
**Excepted quantities (EQ):** Code: E0  
Not permitted as Excepted Quantity  


---

**IMDG:**  
**Limited quantities (LQ):** 1L  
**Excepted quantities (EQ):** Code: E0  
Not permitted as Excepted Quantity  
**Packaging Group:** --  
**UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

**15 Regulatory information**

**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

7727-43-7 | barium sulfate  
108-10-1 | methyl isobutyl ketone

**Toxic Substances Control Act (TSCA):**

All ingredients for this product are found on the inventory list of substances.

**Consumer Product Safety Commission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65 chemicals known to cause cancer:**

13463-67-7 | titanium dioxide  
108-10-1 | methyl isobutyl ketone  
100-41-4 | ethyl benzene  
1333-86-4 | Carbon black

**California Proposition 65 chemicals known to cause birth defects or reproductive harm:**

108-10-1 | methyl isobutyl ketone

**CANADIAN ENVIRONMENTAL PROTECTION ACT:**  
**WHMIS Symbols for Canada:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.  
A - Compressed gas  
D2B - Toxic material causing other toxic effects



**EPA:**

67-64-1 | Acetone

(Contd. on page 5)

## Safety Data Sheet

Printing date 03/17/2017

Revised On 03/10/2017

Trade name: DARK MACHINERY GRAY (ANSI 49)

#MRO88DMG Page 5 of 5

		(Contd. of page 4)
7727-43-7	barium sulfate	D, CBD(inh), NL(oral)
110-19-0	Isobutyl Acetate	D
108-10-1	methyl isobutyl ketone	I

**USDA (United States Department of Agriculture):**

Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product may be used where there is a possibility of incidental food contact.

**16 Other information**

Contact: Regulatory Affairs  
 Date of preparation / last revision 03/17/2017 / -