

## 1 Identification of the substance and manufacturer

**Trade name:** EQUIPMENT YELLOW (NEW)  
**Product code:** MRO88NCY  
**Recommended use:** Paint and coatings application.  
**Uses advised against:** Any that differs from the recommended use.  
**Manufacturer/Supplier:** Seymour of Sycamore  
 917 Crosby Avenue  
 Sycamore, IL 60178 USA  
 phone: 815-895-9101  
 www.seymourpaint.com  
**Emergency telephone number:** 1-800-255-3924

Seymour of Sycamore  
 3041 Dougall Avenue, Suite 503  
 Windsor, ONT N9E 1S3 CANADA  
 phone: 800-435-4482  
 www.seymourpaint.com

## 2 Hazard(s) identification

### Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.  
 Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.  
 Eye Irritation 2A H319 Causes serious eye irritation.  
 Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.  
 Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.  
 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

### Additional information:

### GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

### Signal word

### Hazard statements

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 Suspected of causing cancer. Route of exposure: Inhalation.  
 May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.  
**Precautionary statements**  
 Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store in a well-ventilated place.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

### Chemical characterization: Mixtures

### Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

67-64-1	Acetone	15-25%
74-98-6	propane	15-25%
106-97-8	n-butane	5-10%
7727-43-7	barium sulfate	5-10%
110-19-0	Isobutyl Acetate	5-10%
2807-30-9	Glycol Ether EP	≥5-<10%
123-86-4	butyl acetate	1-5%
108-65-6	PM acetate	1-5%
13463-67-7	titanium dioxide	1-5%
107-87-9	Methyl Propyl Ketone	1-5%

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 2)

Trade name: EQUIPMENT YELLOW (NEW)

(Contd. of page 1)

**After swallowing:** Rinse out mouth and then drink plenty of water.  
Rinse mouth with water. Do not induce vomiting.

**Most important symptoms and effects:** Dizziness

**Indication of any immediate medical attention needed:** No further relevant information available.

**5 Fire-fighting measures**

**Extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.

**Special hazards:** Can form explosive gas-air mixtures.

**Protective equipment for firefighters:** A respiratory protective device may be necessary.

**6 Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Wear protective equipment. Keep unprotected persons away.  
Use respiratory protective device against the effects of fumes/dust/aerosol.

**Methods and material for containment and cleaning up:** Ensure adequate ventilation.

**7 Handling and storage**

**Precautions for safe handling** Use only in well ventilated areas.

**Storage requirements:** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.  
Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV (USA)	Short-term value: 500 ppm
	Long-term value: 250 ppm
	A4, BEI

**74-98-6 propane**

PEL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV (USA)	see Appendix F Minimal oxygen content ( D, EX)

**106-97-8 n-butane**

REL (USA)	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TLV (USA)	Short-term value: 1000 ppm (EX)

**7727-43-7 barium sulfate**

PEL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV (USA)	Long-term value: 5* mg/m <sup>3</sup> *inhalable fraction; E

**110-19-0 Isobutyl Acetate**

PEL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
REL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
TLV (USA)	Short-term value: 150 ppm
	Long-term value: 50 ppm

**123-86-4 butyl acetate**

PEL (USA)	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL (USA)	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm
	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV (USA)	Short-term value: 150 ppm
	Long-term value: 50 ppm

**108-65-6 PM acetate**

WEEL (USA)	Long-term value: 50 ppm
------------	-------------------------

**107-87-9 Methyl Propyl Ketone**

PEL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm
-----------	--

(Contd. on page 3)

Trade name: EQUIPMENT YELLOW (NEW)

(Contd. of page 2)

REL (USA)	Long-term value: 530 mg/m <sup>3</sup> , 150 ppm
TLV (USA)	Short-term value: 150 ppm

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA)	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

**Hygienic protection:** Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:** Nitrile gloves. The glove material must be impermeable and resistant to the substance.

**Eye protection:** Tightly sealed goggles

**9 Physical and chemical properties**

**Appearance:** Aerosol.  
**Odor:** Aromatic  
**Odor threshold:** Not determined.  
**pH-value:** Not determined.  
**Melting point/Melting range:** Undetermined.  
**Boiling point:** -44 °C (-47.2 °F)  
**Flash point:** -19 °C (-2.2 °F)  
**Flammability (solid, gas):** Extremely flammable.  
**Decomposition temperature:** Not determined.  
**Auto igniting:** Product is not self-igniting.  
**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.  
**Lower Explosion Limit:** 1.7 Vol %  
**Upper Explosion Limit:** 10.9 Vol %  
**Vapor pressure:** Not determined.  
**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)  
**Vapor density:** Not determined.  
**Evaporation rate:** Not applicable.  
**Partition coefficient: n-octanol/water:** Not determined.  
**Solubility:** Not determined.  
**Viscosity:** Not determined.  
**Water:** 0.0 %

**10 Stability and reactivity**

**Reactivity:** Stable at normal temperatures.  
**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.  
**Chemical stability:** Not fully evaluated.  
**Possibility of hazardous reactions:** No dangerous reactions known.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

**11 Toxicological information****LD/LC50 values that are relevant for classification:****110-19-0 Isobutyl Acetate**

Oral	LD50	4,763 mg/kg (rbt)
------	------	-------------------

**123-86-4 butyl acetate**

Oral	LD50	14,000 mg/kg (rat)
Inhalative	LC50/4 h	>21 mg/l (rat)

**108-65-6 PM acetate**

Oral	LD50	8,500 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

(Contd. on page 4)

Trade name: EQUIPMENT YELLOW (NEW)

(Contd. of page 3)

13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rbt)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

Information on toxicological effects: No data available.  
Skin effects: No irritant effect.  
Eye effects: Irritating effect.  
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.  
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.  
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.  
  
Bioaccumulative potential: No further relevant information available.  
Mobility in soil: No further relevant information available.  
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
Recommendation: Completely empty cans should be recycled.  
Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950  
DOT UN1950  
DOT Aerosols, flammable  
ADR 1950 Aerosols  
Transport hazard class(es):  
Class 2.1 Gases  
Marine pollutant: No  
Special precautions for user: Warning: Gases  
EMS Number: F-D,S-U  
Packaging Group: --  
UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate

Toxic Substances Control Act (TSCA): All hazardous ingredients are found on the inventory list of substances.  
Canadian Domestic Substances List (DSL): All ingredients are listed or exempted.  
Consumer Product Safety Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7	titanium dioxide
108-10-1	methyl isobutyl ketone
100-41-4	ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

EPA:

67-64-1	Acetone	I
7727-43-7	barium sulfate	D, CBD(inh), NL(oral)
110-19-0	Isobutyl Acetate	D

USDA (United States Department of Agriculture): Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product may be used where there is a possibility of incidental food contact.

(Contd. on page 5)

Trade name: EQUIPMENT YELLOW (NEW)

(Contd. of page 4)

16 Other information

Contact: Regulatory Affairs