



# HAND PROTECTION

## Salt-and-Pepper Cut Resistant Coated Touch Screen Gloves Made with 21-Gauge Tuffalene® Platinum

### DESCRIPTION

These cut-resistant gloves have a 21-gauge salt-and-pepper seamless Tuffalene® Platinum UHMWPE shell. Our innovative Tuffalene® Platinum offers extra comfort, protection, and durability — Free from glass fibers or metal enhancements to achieve this level of cut protection. The palm is coated in black foam nitrile. Features touch screen compatible fingers and a knit wrist cuff to prevent gloves from slipping. Anti-static/electrostatic compliant for use in an ESD protected area.



INDUSTRY		
Aerospace Industry	Demolition	HVAC
Assembly	General Maintenance	Infrastructure Maintenance
Automotive	Glass Handling	Machine Operation
Carpentry	Handling Oily Components	Maintenance
Construction		

### FEATURES

- Component materials comply with FDA regulations for food contact
- 21-gauge ultra-lightweight Tuffalene® Platinum UHMWPE shell offers bare hand sensitivity and cut resistance, free from glass fibers or metal enhancements
- Foam nitrile provides excellent dry, wet, and oily grip with breathability
- Overcast color on hem for easy size identification
- Touch screen compatible fingertips
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use

### SPECIFICATIONS

SHELL	SHELL COLOR	GAUGE	COATING	COATING COLOR	COATING TYPE	FINISH	CUFF	TOUCH SCREEN	FDA FOOD CONTACT
Tuffalene® Platinum UHMWPE	Salt-and-Pepper	21-Gauge	Nitrile	Black	Palm	Foam	Knit Wrist	Yes	Compliant
CUT	ASTM F2992-15 RESULTS	ABRASION	PUNCTURE	PUNCTURE RESULTS	ANTI-STATIC/ELECTROSTATIC	EN 388 LEVELS			
Level A4	1,523 Grams	Level 3	Level 2	54 Newtons	Compliant	3341C			

### PACKAGING

	QUANTITY	6(XS)	7(S)	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	NA	NA	NA	NA	NA	NA
INNER PACK UPC	12/PACK	810033295492	810033295508	810033295515	810033295522	810033295539	810033296437
CASE GTIN	6 PK/CASE	10810033295499	10810033295505	10810033295512	10810033295529	10810033295536	10810033296434
CASE WEIGHT (IN POUNDS)		6.55	7.25	7.7	8.4	8.95	9.65
OVERCAST COLOR		Purple	Red	Green	Brown	Black	Light Blue

### ITEM 5317 SIZES 6(XS)-11(2XL)

- Anti-static/electrostatic compliant
- EN 388 Levels: 3341C

#### Meets ANSI/ISEA 105-2016 standard

- Cut Level A4
- ASTM F2992-15 Results = 1,523 grams
- Abrasion Level 3
- Puncture Level 2
- Puncture Results: 54 Newtons

ABRASION LEVEL

**3**

CUT LEVEL

**A4**

EN 388

3341C

PUNCTURE LEVEL

**2**

ESD COMPLIANT

FDA COMPLIANT

