

NON-FERROUS METAL CLEANER

Aluminum Safe Detergent for Spray Wash Cabinets, Hot Vats and Recirculating Tanks

This product is a highly effective detergent for removing grease, oil, dirt and rust from non-ferrous metal parts (aluminum, zinc, tin). Excellent for use in spray wash cabinets, recirculating tanks and heated immersion tank applications. Suitable for use on all types of metal and painted surfaces.

Directions for Use

Hot Vats and Recirculating Tanks: Dissolve 2-6 ounces of this product per gallon of warm water (approx. 100F). Use at 140-160F.

Spray Wash Cabinets: Dissolve 1/4-1 ounce per gallon of warm water. Overuse may result in poor cleaning performance and/or foaming.

For best cleaning results, use fresh detergent solution in hot, soft water with maximum agitation. Rinse all parts thoroughly after cleaning. Prepare fresh solution frequently to assure maximum cleaning performance.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's can be downloaded from www.crown-chem.com.



Technical Specifications

Appearance	Brown Powder
Odor	Characteristic
pH (1% solution, 22°C)	>11.5
Foaming	Low
Flash Point	NA
Density (lbs/gal)	9.00 ±0.1
Stability Range	NA
Free Alkalinity (as Na ₂ O)	High
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content (as P)	<5.0%

Product Number

#878

Packaging

50 lb. drum
100 lb. drum
300 lb. drum