

# Heavy Duty Presoak Detergent

## Formula 508 Plus

**DESCRIPTION:** Premium alkaline high sudsing powder detergent, formulated especially for frictionless and reduced friction washing.

**ADVANTAGES:**

The extreme versatility of this powder allows it to be used effectively in both touch free in-bay automatics and self service washes.

Can be used as both high pressure detergent and low pressure presoak.

Dissolves easily, stays in solution.

Rinses freely, completely. Leaves no film residue.

Will not dull or streak vehicle finish.

Outstanding cleaning and sudsing ability in the economy of a powder.

Gently penetrates and loosens the most difficult to remove road films from cars and trucks without harming chrome, paint, vinyl tops.

**SPECIFICATIONS:**

Physical Form	Damp powder
Color	Red
Scent	Fresh
Specific Gravity	0.7982
Density	50 lbs. per cu. ft.
Biodegradable	Yes
Foam test 1% Sol.	Initial - 130 mm
pH 2%	12.5
Active Alkalinity	13.45%
Total Alkalinity	20.32%
Total Activity	100%

**DIRECTIONS:**

Final dilution ratio varies depending on application (whether product is being used as a high pressure detergent, low pressure presoak, or as a frictionless step two detergent.)

Start by mixing 3/4 to 1 pound detergent to 1 gallon of water in holding tank. Further dilute through proportioner at a ratio of 17:1 to 23:1.

For "frictionless" automatics dilute to a pH of 10.5 for summer months, and a pH of 11.0 for winter months. A Warsaw Chemical titration kit is recommended to determine accurate strength of solution.

#508PLUS50

**SHIPPING WEIGHT IN POUNDS:**

100 Pound Fiber Drum      103.6 pounds  
 50 Pound Box                      52.1 pounds

